

*Intended Uses:* This latex enamel resists spontaneous ignition when heated by conduction through a metal surface.

### **PRODUCT INFORMATION**

<i>Color:</i>	See Listing	<i>Theoretical Coverage:</i>	700 sq ft @ 1 mil DFT
<i>Gloss:</i>	40-50 @ 60°	<i>Salt Spray Test:</i>	N/A
<i>Volume Solids:</i>	44% minimum	<i>Humidity Test:</i>	N/A
<i>Weight Solids:</i>	58% minimum	<i>Weatherometer Test:</i>	N/A
<i>Weight per Gallon:</i>	11.0-11.4 lbs/gal	<i>Pencil Hardness:</i>	2b @ 72 hours
<i>VOC:</i>	1.3 Lbs/Gal	<i>Viscosity:</i>	99 KU maximum
<i>Film Thickness:</i>	2.0 – 3.0 mils		

### **APPLICATION INFORMATION**

<i>Methods:</i>	Spray (conventional air, airless, AA/A) brush and roller
<i>Mix Ratio:</i>	N/A
<i>Reducer:</i>	Water
<i>Cleaner:</i>	Warm soapy water
<i>Pot Life:</i>	Surface skinning may occur after opening container
<i>Dry Time:</i>	1 hour
<i>Time To Recoat:</i>	8 hours

### **SURFACE PREPARATION**

This enamel is intended for application over previously painted or primed metal surfaces. The surface must be clean, dry and free of loose paint rust, oil and grease. If surface is rusted remove rust and feather painted surface and apply primer. Wait for primer to dry, in accordance with manufactures recommendation, and then apply fire retardant coating. Previously painted surfaces in good condition sand lightly prior to application.

### **SAFETY INFORMATION**

Consult the Material Safety Data Sheet prior to application for detailed information on the health and safety hazards.

**CAUTION:** This Product is for Industrial use Only!

### **STORAGE**

Store in accordance with local, state and federal regulations. Store in a dry area and protect from freezing.,

### **DRY TIME / CURE**

1 hour to touch

### **COMMENTS**

This enamel is not intended to prevent the burning of wood or other combustible substrates. Flame Spread Index 10 maximum (ASTM E-162). Smoke Density 20 maximum (ASTM E-662). This is a VOC compliant product, however it may be thinned with clean water.

***NOTE:*** The above information is supplied as a guideline to our customers. The user must be aware of the cleaning, pretreatment, application and testing requirements for their specific job!